

Model **HLS-230C**



FEATURES

- Prototype & Production Tested Design
- Wide range of options and accessories available
- Simple access for maintenance and operations
- Weatherproof enclosure with 110% fluid containment
- Safety guards for all electrical connections and moving parts
- Lockable latches standard with key
- Engineered vibration dampening system
- Single point lifting bail system
- Galvanized base for long term durability
- Internal silencer and aftertreatment system
- All parts powder coated or galvanized
- Display of all critical operating measures
- Integrated data logging of key operating metrics
- Heavy duty towable design
- Fully programmable controller

Battery System

- Proven LiFePO4 lithium ion battery technology with field proven temperature control system
- Advanced battery management system
- High efficiency alternator and rectifier with low ripple

Engine

- Heavy duty Cat C1.1 engine
- Robust design with modern controls
- Tier 4 Final emissions compliance
- Mechanical fan system
- Complete with engine fluids, ready for operation

Controls

- Standard controls are easy to understand and use
- Control wiring laser labelled
- Remote cellular or satellite telematic ready

UNIT SPECIFICATIONS

Tower Details	23 Feet, Hydraulic / Cable Design
Outriggers	5 Outrigger design with adjustable distances
Battery Capacity	10.4 kW / 230 AH, 48v Nominal
Solar Panel Rating	600 Watts
Containment System Capacity	120% with external drains
Wind Rating	70 MPH, 112 KPH
Axle Type	Torsion Flex Type
Transport Compliance	US DOT and Transport Canada
Coating Type	Galvanized Base and Powder Coated Panels

Model Options Available

- AC inverter package for 120V distribution
- Communications package
- Camera and surveillance ready package
- Arctic package
- Electric block heater
- Communications package
- Customer telematic installation and support
- Customer colors and decal installation

Engine

Manufacturer	Cat
Model	C1.1
Stroke	4
Fuel	Diesel fuel oil
Emissions Compliance	Tier 4 Final
Number and disposition of cylinders	3 Cylinder, Inline
Total Displacement	1.1 Litre, 1,110 CC
Air Intake	Naturally Aspirated
Starting System	12V Dedicated
Speed / Speed Governor	2200 RPM, Electronic Governor
Lube Oil Capacity	4.4 L (4.65 US. qt)
Oil Type <small>(Note: Changes based ambient temp - see manual)</small>	15W-40 Heavy Duty Diesel Engine Oil
Engine Cooling Fan System	Mechanical
Coolant Capacity	5 litres

ALTERNATOR

Compliance	NA
Type	Permanent magnet synchronous generator
Max Speed	2200 RPM
Frequency	NA
Voltage Regulation	RPM Based
Continuous 125/40 ° C Rating	150 Amp
Standby 150/40 ° C Rating	NA
Power Factor	NA
Generator End Efficiency @ 100% Load	Over 93%
Harmonic Distortion	<5%
Alternator IP Protection / Insulation	IP23

APPLICATION DATA

Tower CONTROL PANEL

Model	Enovation Controls
Function	Auto Control Module
Country of Origin	USA

- Backlighting: LED, 900-1000 cd/m2 (30,000 hr lifetime)
- User configurable with PIN protection
- IP rating: IP67, front and back
- RTC: Real-time clock with Li-ion battery backup
- Operating Temperature: -40° to +85°C (-40° to 185°F)
- Build Standards: SAEJ1113, EN61000-6-2, EN12895, ISO 13766



PROTECTIONS

- | | |
|---------------------------|--|
| • Over charging | Battery |
| • Low Oil Pressure | • Over-charging |
| • High Engine Temperature | • Over-discharging. |
| • Start Fail | • State of health monitoring |
| • ECU Diagnostics | • State of charge monitoring |
| • Engine +/- Batt Volts | • Maximum charge current as a charge current limit (CCL) |
| • Over/Under Speed | • Maximum discharge current as a discharge current limit (DCL) |
| • Tamper Proof Hour Meter | • Temperature monitoring |

ENGINE:

- Cast iron block, one piece forged crankshaft
- Pusher type fan with radiator
- Forged connecting rods
- Proven ECM control system
- Long term proven design and longevity
- Global support network
- J1939 Standard Controls and Communication
- Cast iron cylinder heads
- High thermal efficiency
- Designed and capable of long term 24/7 operation
- Standard parts and maintenance kits for lifetime ops
- Premium fuel control system for accurate speed control
- Firing order: 1-2-3
- Displacement: 1.007 liters
- Injection timing E & U & D : 20° BTDC , E1 & U1 : 14° BTDC
- Net Engine Output Rating Standby @ 3600 RPM: 15.7 kW
- Net Engine Output Rating Prime @ 3600 RPM: 14.1 kW
- Coolant capacity (Engine Only) 1.6 liters
- Lub. Method Fully forced pressure feed type



Additional Services Available

- Service Training
- Start Up / Commissioning
- Product and Application Training
- On going product support

Rev E.

3000VA, 2400W Inverter: 2 x 120V GFCI Outlets, 1 x 20 Amp Breaker

DIMENSIONS

